

Amendments to Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (Currently Amended) A device for non-contacting measurement of a length of an object to be measured, in particular a non-abraded length of a sliding contact brush, comprising:

- a pump for producing a variable pneumatic pressure, ~~preferably an oscillating pressure;~~
- a pressurized air line connecting the pump to a nozzle provided in the vicinity of the object to be measured, so that pressurized air from the pump flows through the pressurized air line and the ~~nozzle~~ onto the object to be measured;
- at least one pressure sensor or flow sensor for determining changes of pressure or flow in the pressurized air line; and
- a measuring amplifier or an evaluation circuit connected to the pressure sensor or flow sensor for evaluating signals from the pressure sensor or flow sensor, by means of which amplitudes of fluctuations of measured air pressure and preferably a difference between maximum and minimum air pressure are evaluated.

2. (Currently Amended) A method for non-contacting measurement of ~~path-lengths~~ the lengths of a sliding contact brush, comprising the steps of:

- producing pressurized air having a fluctuating air pressure by means of a pump;
- supplying pressurized air having the fluctuating air pressure via a 30 pressurized air line and a ~~nozzle to an object to be measured~~ said sliding contact brush;
- evaluating fluctuations of the fluctuating air pressure by means of a pressure sensor;
- processing signals from the pressure sensor by means of an amplifier or evaluation circuit, taking account of pressure fluctuations; and
- reading out measurement results of the pressure fluctuations.

Best Available Copy

3. (Currently Amended) A device for determining the length of at least one contact brush in a ~~slide~~ contact track system ~~or collector system~~, comprising:

- a source of pressurized gas;
- means for supplying pressurized gas from the source to the at least one contact brush;
- at least one pneumatic sensor mechanically connected to the at least one brush;
- means for supplying the pneumatic sensor with pressurized gas from the source of pressurized gas; and
- an evaluation unit for evaluating signals from the pneumatic sensor indicating a pressure ~~drop~~ of the pressurized gas, the pressure drop representing a measure of a length of the brush.

4. A device according to claim 3, wherein at least one pneumatic sensor is connected via levers and rod linkages to the brush to be monitored.

5. A device according to claim 3, wherein at least one pneumatic sensor is incorporated in a brush holder adapted to receive the brush.

6. A device according to claim 5, wherein at least one pneumatic sensor comprises at least one flow passage extending parallel to a brush, a length and or cross-section of the flow passage being changed according to a position of the brush.

7. A device according to claim 5, wherein a lateral bore is provided on at least one pneumatic sensor, the bore being normally covered or obstructed by the brush and normally uncovered or unobstructed only when the brush exhibits a certain extent of wear, so that gas can escape through the bore.

8. (Currently Amended) A device according to claim 3, wherein for transfer of pneumatic signals from pneumatic sensors, ~~optionally~~ at least one sensor is provided which is ~~optionally designed to be a~~ pressure sensor or a flow sensor.

9. A device according to claim 3, wherein a plurality of pneumatic sensors are connected to a pressure source by means of a manifold.
10. A device according to claim 9, wherein the manifold has a switching function for selective supply of pressure to particular pneumatic sensors.
11. A device according to claim 3, wherein the pressure source is adapted to be actuated by a ~~click~~.
12. A device according to claim 3, wherein the pressure source is designed to emit pressure ~~pulses~~.
13. A device according to claim 3, wherein the entire pneumatic system is adapted to be purged ~~with~~ gas under increased pressure.
14. A device according to claim 3, wherein a mechanism is provided for adjusting an entire ~~height~~ of a brush block comprising a plurality of brushes according to signals of pneumatic sensors.
15. (Currently Amended) A method for determining the length of at least one contact brush in a ~~sliding contact track system or collector system~~, comprising the steps of:
- feeding a gas into a pneumatic sensor which is ~~preferably~~ adapted to be integrated into a brush holder ~~for and said sensor~~ accommodating the at least one contact brush; and
 - measuring a volume or velocity of gas flowing through the pneumatic sensor, or determining a pressure drop of the gas.
16. (New) A device for non-contacting measurement of a length of an object to be measured, in particular a non-abraded length of a sliding contact brush, comprising:
- a pump for producing a variable pneumatic pressure;
 - a pressurized air line connecting the pump to a nozzle provided in the vicinity of the object to be measured, so that pressurized air from the pump flows through the pressurized air line and the nozzle onto the object to be measured;

- at least one pressure sensor or flow sensor for determining changes of pressure or flow in the pressurized air line; and
- a measuring amplifier or an evaluation circuit connected to the pressure sensor or flow sensor for evaluating signals from the pressure sensor or flow sensor, by means of which amplitudes of fluctuations of measured air pressure are evaluated.

17. (New) A device for non-contacting measurement of a length of an object to be measured, in particular a non-abraded length of a sliding contact brush, comprising:

- a pump for producing a variable pneumatic pressure;
- a pressurized air line connecting the pump to a nozzle provided in the vicinity of the object to be measured, so that pressurized air from the pump flows through the pressurized air line and the nozzle onto the object to be measured;
- at least one pressure sensor or flow sensor for determining changes of pressure or flow in the pressurized air line; and
- a measuring amplifier or an evaluation circuit connected to the pressure sensor or flow sensor for evaluating signals from the pressure sensor or flow sensor, by means of which a difference between maximum and minimum air pressure is evaluated.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.